




YMCA, COLORADO - SHOWN IN ANTIQUE BROWN



Commercial Shingles

Performance Engineered, Sustainably Designed

Aging & Impact Resistant



Best in Class

Malarkey shingles are each *Best in Class* in their respective product categories.

The only complete shingle line [Good-Better-Best] made with the **industry's leading technology** (SBS rubberized asphalt), **highest impact ratings** (Class 3 or Class 4 impact rated – highest ratings possible), **strongest sustainability** (aging longevity, upcycled rubber & plastic, smog-reducing granules), and **superior warranty protection** for peace of mind.

MILL CREEK WEST ELEMENTARY, AMO, INDIANA – SHOWN IN NATURAL WOOD

Made with NEX® Polymer Modified [Rubberized] Asphalt Technology

Asphalt Weathering, Rubber Tough, Environmentally Conscious

Patented NEX® Polymer Modified (SBS Rubberized) Asphalt Technology enhances asphalt's suppleness and stickiness to resist thermal dry-out and aging, and better adhere granules, while adding **rubberlike durability and flex for superior impact resistance, granule adhesion, all-weather resilience, and aging longevity.**

[THE NEX® FORMULA]



High-Grade Asphalt
Waterproofing & Granule Adhesion

+



Synthetic Rubber Polymers (SBS)
Strength, Aging, Flexibility



Upcycled Rubber Polymers
Durability, Aging, Sustainability



Upcycled Plastic Polymers
Strength & Sustainability



Sustainable Performance™

Superior Performance & Better for the Environment

CRAFTSMANSHIP

Up to 2X Larger Nailing Area
Up to 50% More Adhesive Bonds
2X Rain Seals

PERFORMANCE

Up to 35% Greater Tear Strength
Up to 65% Greater Granule Adhesion
Up to Class 4 Impact Rating

SUSTAINABILITY [PER ROOF]¹

Upcycles ~15 Rubber Tires
Upcycles ~9,600 Plastic Bags
Cleans Smog Pollution like ~6 Trees

Color Options

See shingle colors on a roof, or your roof, at www.malarkeyroofing.com/roof-designer.

Distributed from South Gate, CA **[H]** Highlander® **[V]** Vista® **[L]** Legacy® Scotchgard™ Protector
CRRC rated colors can be used to comply with California Energy Code [CEC] Title 24, Part 6 Cool Roof Requirements.
Colors with an SRI of 20 or greater can also be used to comply with Los Angeles County, California Title 31 Cool Roof Requirements.



BLACK OAK [H, V, L]



MIDNIGHT BLACK [H, V, L]



STORM GREY [H, V, L]



WEATHERED WOOD [H, V, L]



NATURAL WOOD [H, V, L]




HEATHER [H, V, L]



ISLAND HOUSE HOTEL, MACKINAC ISLAND, MICHIGAN – SHOWN IN STORM GREY



ANTIQUE BROWN [H, V, L]



TITLE 24 [excludes Legacy®]
TITLE 31 [excludes Legacy®]



SILVERWOOD [H, V, L]



TITLE 24
TITLE 31



GOLDEN AMBER [H]



TITLE 24 [excludes Legacy®]
TITLE 31 [excludes Legacy® and Vista®]



SIENNA BLEND [H, V, L]



TITLE 24
TITLE 31



IVORY MIST [H]



MIAMI UNIVERSITY, OHIO – SHOWN IN MIDNIGHT BLACK

Made Better to Last Longer, & More Sustainable

Malarkey shingles are made with our patented **NEX® Polymer Modified [SBS Rubberized] Asphalt**, an innovative technology that infuses rubber and plastic polymers to strengthen the asphalt core of the shingle for superior impact resistance, granule adhesion, all-weather resilience, and aging longevity.

Malarkey shingles are also sustainable. Upcycled polymers from used tires and plastic bags improve durability and aging resistance, while helping reduce landfill waste. And smog-reducing granules help clean the air of emission pollutants, like planting trees on your roof.

Sustainability without sacrificing performance.



🍀 NEX® RUBBERIZED ASPHALT

Asphalt core of shingle is strengthened with SBS rubber polymers for superior all-weather resilience and aging resistance, then formed around a fiberglass mat, for **up to 35% greater tear strength than the industry standard (ASTM D3462), and up to Class 4 impact rating (highest rating possible)**. *Insurance discounts may apply.*

🍀 UPCYCLED RUBBER & PLASTIC

Polymers from recycled rubber and plastic improve shingle durability and aging resistance, while helping reduce landfill waste. **Each commercial roof of 90 squares upcycles the equivalent of ~15 rubber tires and ~9,600 plastic grocery bags.**¹

🍀 EXTRA, RUBBERIZED RAIN SEAL

2X the rain seals of standard shingles, rubberized with SEBS rubber polymers to improve adhesion, resist dry-out, and provide extra leak protection.

EXTRA, RUBBERIZED LAMINATE BOND

Up to 50% more laminate bonds than standard shingles, rubberized with SEBS rubber polymers to improve adhesion, resist dry-out, and provide extra protection against shingle delamination.

LARGE, RUBBERIZED WIND SEAL

Large wind seal, rubberized with SEBS rubber polymers to improve seal-down adhesion and resist dry-out, helps prevent wind from lifting the shingle up and off the roof. **Wind warranty up to 130 mph.**

It takes 18,000 nails to secure a commercial roof. Even one out of place can cause a leak.


🍀 THE ZONE® LARGER NAILING AREA

Up to 2X larger nailing area dramatically improves installation speed and accuracy, and helps ensure nails secure BOTH shingle layers – critical for preventing blow-offs.

🍀 LONGER & TAPERED BACKING SHIM

Longer, tapered shingle backing helps ensure nails penetrate BOTH shingle layers (critical for preventing blow-offs), promotes water flow, and helps prevent rain from blowing under the shingle and pooling (troughing), waiting to leak down a misplaced nail.



Side View:



Top View:

Malarkey Shingle

Standard Shingle



Wider

Longer

Nail misses back layer.

Nail misses back shingle layer causing leak.



CERAMIC-COATED GRANULES

3M™ Roofing Granules add color vibrancy and protect the shingle from hail impact and UV aging, while NEX® Rubberized Asphalt dramatically improves granule retention. **Up to 65% greater granule adhesion than the industry standard (ASTM D3462).**



🍀 SMOG-REDUCING GRANULES

Blend of photocatalytic 3M™ Smog-Reducing Granules harness sunlight to actively clean the air of emission pollutants. **Each commercial roof of 90 squares has the smog-fighting potential of ~6 trees.**²



ALGAE-RESISTANT GRANULES


Blend of algae-resistant 3M™ Copper Granules help prevent black streaks caused by algae growth. **Up to a Limited Lifetime Algae Warranty** [only on Legacy® shingle line].

🍀 Malarkey Industry Firsts


	VERY GOOD	BETTER	BEST
Architectural Shingle Lines Comparison Chart	Highlander®	Vista®	Legacy® Scotchgard™ Protector
Rubberized Asphalt Technology	NEX ¹	NEX ¹	NEX ¹
Impact Rating [Class 4 Highest]	Class 3	Class 4	Class 4
Fire Rating [Class A Highest]	Class A	Class A	Class A
Tear Strength*	+10%	+25%	+35%
Thickness		+10%	+19%
Sustainability [assumes roof of 90 squares]			
~Upcycled Rubber Tires	12	15	18
~Upcycled Plastic Bags	8,700	9,600	12,000
~Trees 'Planted' ²	6	6	6
Cost	\$	\$\$	\$\$\$
Warranties*:			
Shingle Warranty [years]	40	40	50
Non-Prorated Period [years]	10	15	20
Algae Warranty	NA	NA	Limited Lifetime**
Standard Wind Warranty [mph / kph / years]	110 / 177 / 15	110 / 177 / 15	110 / 177 / 15
Enhanced Wind Warranty [mph / kph / years]	130 / 209 / 15	130 / 209 / 15	130 / 209 / 15

*Versus standard shingles, as measured per ASTM D3462. **Included on shingles with Scotchgard™ Protector from 3M.

IMPACT RESISTANCE COMPARISON



Standard shingles are brittle, more likely to fracture and lose granules from hail impact.



Malarkey shingles are rubberized to better absorb and deflect hail impact.



¹ Assumes roof of 90 squares using Vista® shingles.

² Assumes roof of 90 squares. Source: Lawrence Berkeley National Laboratory and 3M.
TEST COMPLIANCE: All Shingles - ASTM D7158 Class H, ASTM D3462, ASTM D3161 Class F, ASTM D3018 Type I, ASTM E108 Class A Fire Rating, CSA A123.5, ICC Approval - ESR-3150, and ICC-ES AC438. UL 2218 Class 4 (Legacy® and Vista® lines) and UL 2218 Class 3 (Highlander® line). CRRC-rated colors can be used to comply with California Energy Code [CEC] Title 24, Part 6 Cool Roof Requirements (Highlander® Golden Amber, Ivory Mist, Sienna Blend, and Silverwood, and Vista® Sienna Blend and Silverwood). Highlander® Golden Amber, Ivory Mist, Sienna Blend, and Silverwood, and Vista® Silverwood shingles can also be used to comply with Los Angeles County, California Title 31 Cool Roof Requirements.

DISCLAIMER: Photographs of shingles may not accurately represent their true color or the variations of color blends that will appear on the roof. **Before installation, five or six shingles should be laid out and reviewed for desired color.** Colors and specifications subject to change without notice. Shingle colors not available in all regions or product lines. Scotchgard and Scotchgard Protector, including the 3M logo, are all trademarks of 3M.

+ For complete warranty information, please reference Malarkey's **Shingle and Accessory Warranty** available at www.malarkeyroofing.com/warranties.

This version supersedes all previous versions. Rev. 04/24

www.malarkeyroofing.com

