


Made with NEX® Polymer Modified (Rubberized) Asphalt Technology

Asphalt Weathering, Rubber Tough, Environmentally Conscious

Patented NEX* Polymer Modified (SBS Rubberized) Asphalt Technology enhances asphalt's suppleness and stickiness to resist thermal dry-out and aging, and better adhere granules, while adding **rubberlike durability and flex for superior impact resistance**, **granule adhesion**, **all-weather resilience**, **and aging longevity**.

[THE NEX® FORMULA]



High-Grade AsphaltWaterproofing & Granule Adhesion



Upcycled Rubber Polymers Durability, Aging, Sustainability



Synthetic Rubber Polymers (SBS) Strength, Aging, Flexibility



Upcycled Plastic Polymers Strength & Sustainability



Sustainable Performance™

Superior Performance & Better for the Environment

CRAFTSMANSHIP

Up to 2X Larger Nailing Area Up to 50% More Adhesive Bonds 2X Rain Seals

PERFORMANCE

Up to 35% Greater Tear Strength Up to 65% Greater Granule Adhesion Up to Class 4 Impact Rating

SUSTAINABILITY


(PER ROOF)1

Upcycles ~15 Rubber Tires Upcycles ~9,600 Plastic Bags Cleans Smog Pollution like ~6 Trees

Color Options

See shingle colors on a roof, or your roof, at www.malarkeyroofing.com/roof-designer.

Distributed from Oklahoma City, OK **(H)** Highlander® AR **(V)** Vista® AR **(L)** Legacy® Scotchgard™ Protector Matching colors available in high-profile EZ-Ridge® XT as well as standard low-profile RidgeFlex® hip and ridge shingles.



Made Better to Last Longer, & More Sustainable

Malarkey shingles are made with our patented NEX® Polymer Modified (SBS Rubberized) Asphalt, an innovative technology that infuses rubber and plastic polymers to strengthen the asphalt core of the shingle for superior impact resistance, granule adhesion, all-weather resilience, and aging longevity.

Malarkey shingles are also sustainable. Upcycled polymers from used tires and plastic bags improve durability and aging resistance, while helping reduce landfill waste. And smoq-reducing granules help clean the air of emission pollutants, like planting trees on your roof.

Sustainability without sacrificing performance.







NEX® RUBBERIZED ASPHALT


Asphalt core of shingle is strengthened with SBS rubber polymers for superior all-weather resilience and aging resistance, then formed around a fiberglass mat, for up to 35% greater tear strength than the industry standard (ASTM D3462), and up to Class 4 impact rating (highest rating possible). Insurance discounts may apply.

It takes 18,000 nails to secure a commercial roof. Even one out of place can cause a leak.


***** THE ZONE® LARGER NAILING AREA

Up to 2X larger nailing area dramatically improves installation speed and accuracy, and helps ensure nails secure BOTH shingle layers - critical for preventing blow-offs.

Top View:



Standard Shingle




STANDARD NAILING AREA

\$ LONGER & TAPERED BACKING SHIM

Longer, tapered shingle backing helps ensure and pooling (troughing), waiting to leak down a

Side View:



\$ UPCYCLED RUBBER & PLASTIC

Polymers from recycled rubber and plastic improve shingle durability and aging resistance, while helping reduce landfill waste. Each commercial roof of 90 squares upcycles the equivalent of ~15 rubber tires and ~9,600 plastic grocery bags.1

RFID TAG (1 per 3-4 bundles) Aides shingle identification, quality improvement, and lifecycle analysis.

DAT DIAR

2 RAIN SEALS

1-5/16"

3 LAMINATE BONDS

nails penetrate BOTH shingle layers (critical for preventing blow-offs), promotes water flow, and helps prevent rain from blowing under the shingle misplaced nail.


CERAMIC-COATED GRANULES

Roofing Granules add color vibrancy and protect the shingle from hail impact and UV aging, while NEX® Rubberized Asphalt dramatically improves granule retention. Up to 65% greater granule adhesion than the industry standard (ASTM D3462).



SMOG-REDUCING GRANULES

Blend of photocatalytic 3M™ Smog-Reducing Granules harness sunlight to actively clean the air of emission pollutants. **Each** commercial roof of 90 squares has the smoq-fighting potential of ~6 trees.2



\$ EXTRA, RUBBERIZED RAIN SEAL

rubberized with SEBS rubber polymers to improve adhesion, resist dry-out, and provide extra leak protection.

EXTRA, RUBBERIZED LAMINATE BOND

Up to 50% more laminate bonds than standard shingles, rubberized with SEBS rubber polymers to improve adhesion, resist dry-out, and provide extra protection against shingle delamination.

LARGE, RUBBERIZED WIND SEAL

Large wind seal, rubberized with SEBS rubber polymers to improve seal-down adhesion and resist dry-out, helps prevent wind from lifting the shingle up and off the roof. Wind warranty up to 130 mph.



ALGAE-RESISTANT GRANULES


Blend of algae-resistant 3M™ Copper Granules help prevent black streaks caused by algae growth. Up to a Limited Lifetime Algae Warranty.




Malarkev Industry Firsts

Architectural Shingle Lines Comparison Chart	Highlander® AR	Vista® AR	Legacy® Scotchgard™ Protector
Rubberized Asphalt Technology	ИЕХ.	Ŋ E X.	NEX.
Impact Rating (Class 4 Highest)	Class 3	Class 4	Class 4
Fire Rating (Class A Highest)	Class A	Class A	Class A
Tear Strength*	+10%	+25%	+35%
Thickness		+10%	+19%
Sustainability (assumes roof of 90 squares)			
~Upcycled Rubber Tires	12	15	18
~Upcycled Plastic Bags	8,700	9,600	12,000
~Trees 'Planted' ²	6	6	6
Cost	\$	\$\$	\$\$\$
Warranties*:			
Shingle Warranty (years)	40	40	50
Non-Prorated Period (years)	10	15	20
Algae Warranty (years)	10	15	Limited Lifetime**
Standard Wind Warranty [mph / kph / years]	110 / 177 / 15	110 / 177 / 15	110 / 177 / 15
Enhanced Wind Warranty (mph / kph / years)	130 / 209 / 15	130 / 209 / 15	130 / 209 / 15
*Versus standard shingles, as measured per ASTM D3462.	. **Included on shingles with Scotchgard™ Protector from 3M.		

IMPACT RESISTANCE COMPARISON



Standard shingles are brittle, more likely to fracture and lose granules from hail impact.



Malarkey shingles are rubberized to better absorb and deflect hail impact.













- ¹ Assumes roof of 90 squares using Vista*shingles.
- ² Assumes roof of 90 squares. Source: Lawrence Berkeley National Laboratory and 3M.

TEST COMPLIANCE: All Shingles - ASTM D7158 Class H, ASTM D3462, ASTM D3161 Class F, ASTM D3018 Type I, ASTM E108 Class A Fire Rating, CSA A123.5, ICC Approval - ESR-3150, and ICC-ES AC438. FBC Approval #14809 (Legacy* and Vista* lines) and FBC Approval - FL36890 (Highlander* line), UL 2218 Class 4 (Legacy* and Vista* lines) and UL 2218 Class 3 (Highlander* line).

DISCLAIMER: Photographs of shingles may not accurately represent their true color or the variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for desired color. Colors and specifications subject to change without notice. Shingle colors not available in all regions or product lines. Scotchgard and Scotchgard Protector, including the 3M logo, are all trademarks of 3M.

+ For complete warranty information, please reference Malarkey's **Shingle and Accessory Warranty available at www.malarkeyroofing.com/warranties**.

This version supersedes all previous versions. Rev. 03/24

www.malarkeyroofing.com







